

**Two Stroke**

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier**

Product Name Two Stroke
Product code 0120, 0118, 0176, 0271, 0206
Unique Formula Identifier (UFI) KUM0-T04K-200V-6N7Q

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) PC24 Lubricants, greases, release products
Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet**Manufacturer**

Company Identification Granville Oil & Chemicals Ltd
Address of Manufacturer 29 Goldthorpe Ind. Est.,
Goldthorpe,
Rotherham,
South Yorkshire,

Postal code S63 9BL
Telephone: +44 (0)1709 890099
Fax Not known.

E-mail lab@granvilleoil.com

Office hours 08:00 - 17:00

Supplier

Company Identification Veedol Deutschland GmbH
Address of Supplier Hans-Böckler-Straße 10
Langenfeld,
Germany

Postal code 40764
Telephone: +49 (0) 2173 893 30 30
Fax Not known.
E-mail lab@granvilleoil.com
Office hours

1.4 Emergency telephone number

Emergency Phone No. +44 (0)1709 890099
Contact Granville Lab
National response centre
Address NHS Direct
Emergency Phone No. +44 111

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

**Two Stroke**

Regulation (EC) No. 1272/2008 (CLP) Flam. Liq. 3 :Flammable liquid and vapour.
Skin Irrit. 2 :Causes skin irritation.
Aquatic Chronic 3 :Harmful to aquatic life with long lasting effects.

2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP)

Product Name Two Stroke
Contains Kerosine

Hazard Pictogram(s)



GHS02



GHS07

Signal Word(s) Warning

Hazard Statement(s) H226: Flammable liquid and vapour.
H315: Causes skin irritation.
H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s) P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273: Avoid release to the environment.
P403+P235: Store in a well-ventilated place. Keep cool.
P501: Dispose of contents in accordance with local, state or national legislation.

Unique Formula Identifier (UFI) KUM0-T04K-200V-6N7Q

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substances**

Not applicable.

3.2 Mixtures



Two Stroke

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / REACH Registration No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Kerosine (petroleum) Straight run kerosine [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150 °C to 290 °C (320 °F to 554 °F).]	8008-20-6	232-366-4	9-12	Flam. Liq. 3 H226 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411	GHS02 GHS08 GHS07 GHS09
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar''-Me derivs.	92257-31-3	296-120-8	<1	Repr. 2 H361f STOT RE 2 H373 Aquatic Chronic 4 H413	GHS08
Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts		939-603-7 01- 2119978241- 36- XXXX	<0.5	Not classified	None
Distillates (petroleum), hydrotreated light naphthenicBaseoil - unspecified[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]	64742-53-6	265-156-6 01- 2119480375- 34-xxxx	<0.5	Asp. Tox. 1 H304	GHS08
Calcium dihydroxide	1305-62-0	215-137-3 01- 2119475151- 45- XXXX	<0.5	Skin Irrit. 2 H315 Eye Dam. 1 H318 STOT SE 3 H335	GHS05 GHS07
diphenylamine	122-39-4	204-539-4 01- 2119488966- 13- XXXX	<0.5	Acute Tox. 3 H301 Acute Tox. 3 H311 Acute Tox. 3 H331 STOT RE 2 H373 Aquatic Acute 1 H400 Aquatic Chronic 1 H410	GHS06 GHS08 GHS09

**Two Stroke**

HAZARDOUS INGREDIENT(S)	CAS No.	Specific Concentration Limit	M-factor	ATE
diphenylamine	122-39-4			Acute Tox. 3 (H301) : 100 Acute Tox. 3 (H311) : 300 Acute Tox. 3 (H331) : 3.000

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin Contact	Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. Take off immediately all contaminated clothing. Rinse skin with water.
Eye Contact	Flush eyes with water for at least 15 minutes.
Ingestion	Wash out mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

May cause irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment (see Medical Advice on this label). Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

Suitable Extinguishing media	Foam, CO ₂ or dry Powder.
Unsuitable extinguishing media	Do not use water.

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. Combustion or thermal decomposition will evolve toxic and irritant vapours.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

**Two Stroke**

Provide adequate ventilation. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Wear suitable protective clothing, gloves and eye/face protection.

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Adsorb spillages onto sand, earth or any suitable adsorbent material. Contain spillages with sand, earth or any suitable adsorbent material. Earth may be shovelled to contain spillage and to avoid contamination of sewers and watercourses.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use explosion-proof electrical equipment. Use non-sparking tools. Take action to prevent static discharges. Wash hands and exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep cool.

Storage temperature

Ambient.

Storage life

Stable under normal conditions.

Incompatible materials

None known.

7.3 Specific end use(s)

PC24 Lubricants, greases, release products

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters**

8.1.1 Occupational Exposure Limits

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Calcium hydroxide	1305-62-0		5			
Calcium hydroxide - Respirable fraction	1305-62-0		1		4	
Diphenylamine	122-39-4		10		20	



Two Stroke

Region Source
United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes

8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection Normally no personal respiratory protection is necessary. Handling of larger amounts A suitable mask with filter may be appropriate.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Red.
Odour	Characteristic odour
Melting point/freezing point	Not known.
Boiling point or initial boiling point and boiling range	Not known.
Flammability	Not known.
Lower and upper explosion limit	Not known.
Flash Point	=>23 °C
Auto-ignition temperature	Not known.
Decomposition Temperature	Not known.
pH	Not known.
Kinematic Viscosity	=>40 mm ² /s 40 °C
Solubility	Solubility (Water): Insoluble. Solubility (Other): Not known.

**Two Stroke**

Partition coefficient n-octanol/water (log value)	Not known.
Vapour pressure	Not known.
Density and/or relative density	0.879 g/cm ³ - Relative density : 15 °C
Relative vapour density	Not known.
Particle characteristics	Not known.

9.2 Other information

None.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Avoid friction, sparks, or other means of ignition.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity - Ingestion	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 1000000
Acute toxicity - Skin Contact	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 1000000
Acute toxicity - Inhalation	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 136363.64
Skin corrosion/irritation	Calculation method : Causes skin irritation.
Serious eye damage/irritation	Calculation method : Not classified.
Skin sensitization data	Calculation method : Not classified.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified.
Carcinogenicity	Calculation method : Not classified.
Reproductive toxicity	Calculation method : Not classified.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : Not classified.
STOT - repeated exposure	Calculation method : Not classified.

**Two Stroke**

Aspiration hazard

Calculation method : Not classified.

11.2 Information on other hazards

Not known.

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity**

Harmful to aquatic life with long lasting effects.

Toxicity - Aquatic invertebrates

Not known.

Toxicity - Fish

Not known.

Toxicity - Algae

Not known.

Toxicity - Sediment Compartment

Not classified.

Toxicity - Terrestrial Compartment

Not classified.

12.2 Persistence and degradability

Not known.

12.3 Bioaccumulative potential

Not known.

12.4 Mobility in soil

Not known.

12.5 Results of PBT and vPvB assessment

Not known.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Dispose of contents in accordance with local, state or national legislation. Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Do not allow to enter drains, sewers or watercourses. Do NOT landfill. Normal disposal is via incineration operated by an accredited disposal contractor. Send to a licensed recycler, reclaimer or incinerator. Dispose of this material and its container to hazardous or special waste collection point. Dispose at suitable refuse site.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION**14.1 UN number or ID number**

UN No.

1993

**Two Stroke****14.2 UN proper shipping name**

UN proper shipping name FLAMMABLE LIQUID, N.O.S.

14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 3
ADR Classification Code F1
Special Provisions 274 601
Limited Quantities 5 L
Excepted Quantities E1
Emergency Action Code •3Y
Mixed Packing Instructions for Packages P001 IBC03 LP01 R001
Special Packing Provisions for Packages

Mixed Packing Instructions for Packages MP19
Packing Instructions for Portable Tanks T4
Special Provisions for Portable Tanks TP1 TP29
Tank Code for Tanks LGBF
Special Provisions for Tanks

Vehicle for Tank Carriage FL
ADR Transport Category 3
Tunnel Restriction Code D/E
Special Provisions for Carriage - Packages V12
Special Provisions for Carriage - Bulk

Special Provisions for Carriage - Loading,
Unloading and Handling

Special Provisions for Carriage - Operation S2
ADR HIN 30

IMDG

IMDG Class 3
Special Provisions 274 601
Limited Quantities 5 L
Excepted Quantities E1
Mixed Packing Instructions for Packages P001 IBC03 LP01 R001
Special Packing Provisions for Packages

Packing Instructions for Portable Tanks T4
Special Provisions for Portable Tanks TP1 TP29
IMDG EMS F-E, S-E
Stowage and Handling Category A
Segregation

Marine Pollutant

ICAO/IATA

IATA Proper Shipping Name FLAMMABLE LIQUID, N.O.S.
Excepted Quantities E1

**Two Stroke**

Passenger and Cargo Aircraft Limited	Y344
Quantities Packing Instructions	
Passenger and Cargo Aircraft Limited	10L
Quantities Max net Qty	
Passenger and Cargo Aircraft Packing	355
Instructions	
Passenger and Cargo Aircraft Max net	60L
Qty	
Cargo Aircraft Packing Instructions	366
Cargo Aircraft Max net Qty	220L
Special Provisions	A3
Emergency Response Guidebook (ERG)	3L
Code	
Labels	
Labels	3

**14.4 Packing group**

Packing group III

14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Maritime transport in bulk according to IMO instruments

No information available

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very High Concern for Authorisation Not listed

REACH: ANNEX XIV list of substances subject to authorisation Not listed

REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Carcinogens: category 1B (64742-53-6), Kerosine (petroleum) Straight run kerosine [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150 °C to 290 °C (320 °F to 554 °F).] (8008-20-6), Calcium dihydroxide (1305-62-0), diphenylamine (122-39-4), 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. (92257-31-3)

Community Rolling Action Plan (CoRAP) Not listed

**Two Stroke**

Regulation (EU) N° 2019/1021 of the European Parliament and of the Council on persistent organic pollutants Not listed

Regulation (EC) N° 1005/2009 on substances that deplete the ozone layer Not listed

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Diphenylamine (122-39-4)

National regulations

Other Not known.

15.2 Chemical Safety Assessment

A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s)



GHS02



GHS07

GHS05: GHS: Corrosion

GHS06: GHS: Skull and crossbones

GHS08: GHS: Health hazard

GHS09: GHS: Environment

Hazard classification

Flam. Liq. 3 : Flammable liquid, Category 3

Acute Tox. 3 : Acute toxicity, Category 3

Asp. Tox. 1 : Aspiration hazard, Category 1

Acute Tox. 3 : Acute toxicity, Category 3

Skin Irrit. 2 : Skin corrosion/irritation, Category 2

Eye Dam. 1 : Serious eye damage/irritation, Category 1

Acute Tox. 3 : Acute toxicity, Category 3

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Repr. 2 : Reproductive toxicity, Category 2

STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2



Two Stroke

Aquatic Acute 1 : Hazardous to the aquatic environment, Acute, Category 1
Aquatic Chronic 1 : Hazardous to the aquatic environment, Chronic, Category 1
Aquatic Chronic 2 : Hazardous to the aquatic environment, Chronic, Category 2
Aquatic Chronic 3 : Hazardous to the aquatic environment, Chronic, Category 3
Aquatic Chronic 4 : Hazardous to the aquatic environment, Chronic, Category 4

Hazard Statement(s)

H226: Flammable liquid and vapour.
H301: Toxic if swallowed.
H304: May be fatal if swallowed and enters airways.
H311: Toxic in contact with skin.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H331: Toxic if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H361f: Suspected of damaging fertility.
H373: May cause damage to organs through prolonged or repeated exposure.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.
H413: May cause long lasting harmful effects to aquatic life.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical equipment.
P242: Use non-sparking tools.
P243: Take action to prevent static discharges.
P264: Wash hands and exposed skin thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P321: Specific treatment (see Medical Advice on this label).



Two Stroke

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use water spray, dry powder or carbon dioxide to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CAS : Chemical Abstracts Service

CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

DNEL : Derived No Effect Level

EC : European Community

EINECS : European Inventory of Existing Commercial Chemical Substances

IATA : International Air Transport Association

IBC : Intermediate Bulk Container

ICAO : International Civil Aviation Organization

IMDG : International Maritime Dangerous Goods

LTEL : Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for Regulation (EC) No. 1272/2008 (CLP) data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Granville Oil & Chemicals Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Granville Oil & Chemicals Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.