

Gunk Engine Degreasant - Aerosol

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier**

Product Name Gunk Engine Degreasant - Aerosol
Product code 6731
Unique Formula Identifier (UFI) G610-Y0CE-M00G-NJSQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Intended for general public
Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet**Manufacturer**

Company Identification Granville Oil & Chemicals Ltd
Address of Manufacturer 29 Goldthorpe Ind. Est.,
Goldthorpe,
Rotherham,
South Yorkshire,

Postal code S63 9BL

Telephone: +44 (0)1709 890099

Fax Not known.

E-mail lab@granvilleoil.com

Office hours 08:00 - 17:00

Supplier

Company Identification Veedol Deutschland GmbH
Address of Supplier Hans-Böckler-Straße 10
Langenfeld,
Germany

Postal code 40764

Telephone: +49 (0) 2173 893 30 30

Fax Not known.

E-mail lab@granvilleoil.com

Office hours

1.4 Emergency telephone number

Emergency Phone No. +44 (0)1709 890099

Contact Granville Lab

National response centre

Address NHS Direct

Emergency Phone No. +44 111

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Gunk Engine Degreasant - Aerosol

Regulation (EC) No. 1272/2008 (CLP) Aerosol 1 :Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2 :Causes skin irritation.
Eye Irrit. 2 :Causes serious eye irritation.
STOT SE 3 :May cause drowsiness or dizziness.
Aquatic Chronic 2 :Toxic to aquatic life with long lasting effects.

2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP)

Product Name Gunk Engine Degreasant - Aerosol
Contains REGULAR KEROSENE; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,
<2% aromatics

Hazard Pictogram(s)



GHS02



GHS07



GHS09

Signal Word(s)

Danger

Hazard Statement(s)

H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P271: Use only outdoors or in a well-ventilated area.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Unique Formula Identifier (UFI)

G610-Y0CE-M00G-NJSQ

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Gunk Engine Degreasant - Aerosol**3.1 Substances**

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / REACH Registration No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Petroleum gases, liquefied Petroleum gas [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately -40 °C to 80 °C (-40 °F to 176 °F).]	68476-85-7	270-704-2	50-70	Flam. Gas 1A H220	GHS02
Kerosine (petroleum) Straight run kerosine [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150 °C to 290 °C (320 °F to 554 °F).]	8008-20-6	232-366-4	10-30	Flam. Liq. 3 H226 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Chronic 2 H411	GHS02 GHS08 GHS07 GHS09
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	919-857-5	10-30	Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H336	GHS02 GHS08 GHS07
Alcohols, C12-14, ethoxylated	68439-50-9	500-213-3	1-10	Eye Dam. 1 H318 Aquatic Chronic 3 H412	GHS05

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

Inhalation

Remove person to fresh air and keep comfortable for breathing.

Skin Contact

Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Gunk Engine Degreasant - Aerosol

Ingestion Call a poison center or a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

May cause irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

Suitable Extinguishing media Water spray. Dry powder. Foam. Carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Fire hazard Extremely flammable aerosol.
Explosion hazard Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire Toxic fumes may be released.

5.3 Advice for firefighters

Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Emergency procedures Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Protective equipment Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2 Environmental precautions

Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Precautions for safe handling Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Gunk Engine Degreasant - Aerosol

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
 Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3 Specific end use(s)

Not known.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters**

8.1.1 Occupational Exposure Limits

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTTEL (8 hr TWA ppm)	LTTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Liquefied petroleum gas	68476-85-7	1000	1750	1250	2180	(f)

Region Source
 United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes
 (f) Carc (only applies if LPG contains more than 0.1% of buta-1,3-diene)

8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Physical state Aerosol
 Colour Clear.

Gunk Engine Degreasant - Aerosol

Odour	Characteristic.
Melting point/freezing point	Not known.
Boiling point or initial boiling point and boiling range	Not applicable.
Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	Not known.
Flash Point	< 23 °C
Auto-ignition temperature	Not known.
Decomposition Temperature	Not known.
pH	Not known.
Kinematic Viscosity	Not known.
Solubility	Solubility (Water) : Not known. Solubility (Other) : Not known.
Partition coefficient n-octanol/water (log value)	Not known.
Vapour pressure	Not known.
Density and/or relative density	Not known.
Relative vapour density	Not known.
Particle characteristics	Not known.
Explosive properties	Pressurised container: May burst if heated.
9.2 Other information	None.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity - Ingestion	Calculation method : Not classified.
Acute toxicity - Skin Contact	Calculation method : Not classified.
Acute toxicity - Inhalation	Calculation method : Not classified.
Skin corrosion/irritation	Calculation method : Causes skin irritation.

Gunk Engine Degreasant - Aerosol

Serious eye damage/irritation	Calculation method : Causes serious eye irritation.
Skin sensitization data	Calculation method : Not classified.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified.
Carcinogenicity	Calculation method : Not classified.
Reproductive toxicity	Calculation method : Not classified.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : May cause drowsiness or dizziness.
STOT - repeated exposure	Calculation method : Not classified.
Aspiration hazard	Self classification: Not classified.

11.2 Information on other hazards

Not known.

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity**

Toxic to aquatic life with long lasting effects.

Toxicity - Aquatic invertebrates	Not known.
Toxicity - Fish	Not known.
Toxicity - Algae	Not known.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.

12.2 Persistence and degradability

Not known.

12.3 Bioaccumulative potential

Not known.

12.4 Mobility in soil

Not known.

12.5 Results of PBT and vPvB assessment

Not known.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Dispose of contents in accordance with local, state or national legislation. Send to a licensed recycler, reclaimer or incinerator. Dispose of this material and its container to hazardous or special waste collection point. Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Do not allow to enter drains, sewers or watercourses. Do NOT landfill.

13.2 Additional Information

Gunk Engine Degreasant - Aerosol

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION**14.1 UN number or ID number**

UN No. 1950

14.2 UN proper shipping name

UN proper shipping name AEROSOLS

14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 2

ADR Classification Code 5F

Special Provisions 190 327 344 625

Limited Quantities 1 L

Excepted Quantities E0

Emergency Action Code

Mixed Packing Instructions for Packages P207 LP200

Special Packing Provisions for Packages PP87 RR6 L2

Mixed Packing Instructions for Packages MP9

Packing Instructions for Portable Tanks

Special Provisions for Portable Tanks

Tank Code for Tanks

Special Provisions for Tanks

Vehicle for Tank Carriage

ADR Transport Category 2

Tunnel Restriction Code D

Special Provisions for Carriage - V14

Packages

Special Provisions for Carriage - Bulk

Special Provisions for Carriage - Loading, CV9 CV12

Unloading and Handling

Special Provisions for Carriage - S2

Operation

ADR HIN

IMDG

IMDG Class 2

Special Provisions 190 327 344 625

Limited Quantities 1 L

Excepted Quantities E0

Mixed Packing Instructions for Packages P207 LP200

Special Packing Provisions for Packages PP87 RR6 L2

Packing Instructions for Portable Tanks

Special Provisions for Portable Tanks

IMDG EMS F-D, S-U

Stowage and Handling SW1 SW22

Gunk Engine Degreasant - Aerosol

Segregation	SG69
Marine Pollutant	
ICAO/IATA	
IATA Proper Shipping Name	AEROSOLS
Excepted Quantities	E0
Passenger and Cargo Aircraft Limited	Y203
Quantities Packing Instructions	
Passenger and Cargo Aircraft Limited	30Kg G
Quantities Max net Qty	
Passenger and Cargo Aircraft Packing	203
Instructions	
Passenger and Cargo Aircraft Max net Qty	75Kg
Cargo Aircraft Packing Instructions	203
Cargo Aircraft Max net Qty	150Kg
Special Provisions	A145, A167, A802
Emergency Response Guidebook (ERG)	10L
Code	
Labels	
Labels	2.1

**14.4 Packing group**

Packing group

14.5 Environmental hazards

Environmental hazards Classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Maritime transport in bulk according to IMO instruments

No information available

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very High Concern for Authorisation Not listed

High Concern for Authorisation

REACH: ANNEX XIV list of substances subject to authorisation Not listed

REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Carcinogens: category 1A (68476-85-7), Mutagens: category 1B (64742-48-9), Kerosine (petroleum) Straight run kerosine [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150 °C to 290 °C (320 °F to 554 °F).] (8008-20-6), Alcohols, C12-14, ethoxylated (68439-50-9)

Gunk Engine Degreasant - Aerosol

Community Rolling Action Plan (CoRAP) Not listed
 Regulation (EU) N° 2019/1021 of the European Parliament and of the Council on persistent organic pollutants Not listed
 Regulation (EC) N° 1005/2009 on substances that deplete the ozone layer Not listed
 Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Not listed

National regulations

Other Not known.

15.2 Chemical Safety Assessment

A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s)



GHS02



GHS07



GHS09

GHS05: GHS: Corrosion

GHS08: GHS: Health hazard

Hazard classification

Flam. Gas 1A : Flammable gas Category 1A

Aerosol 1 : Aerosol, Category 1

Flam. Liq. 3 : Flammable liquid, Category 3

Asp. Tox. 1 : Aspiration hazard, Category 1

Skin Irrit. 2 : Skin corrosion/irritation, Category 2

Eye Dam. 1 : Serious eye damage/irritation, Category 1

Eye Irrit. 2 : Serious eye damage/irritation, Category 2

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Aquatic Chronic 2 : Hazardous to the aquatic environment, Chronic, Category 2

Aquatic Chronic 3 : Hazardous to the aquatic environment, Chronic, Category 3

Hazard Statement(s)

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H226: Flammable liquid and vapour.

Gunk Engine Degreasant - Aerosol

H229: Pressurised container: May burst if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTRE/doctor if you feel unwell.

P321: Specific treatment (see Medical Advice on this label).

P332+P313: If skin irritation occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P391: Collect spillage.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CAS : Chemical Abstracts Service

CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of

Gunk Engine Degreasant - Aerosol

substances and mixtures

DNEL : Derived No Effect Level

EC : European Community

EINECS : European Inventory of Existing Commercial Chemical Substances

IATA : International Air Transport Association

IBC : Intermediate Bulk Container

ICAO : International Civil Aviation Organization

IMDG : International Maritime Dangerous Goods

LTEL : Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for Regulation (EC) No. 1272/2008 (CLP)
data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Granville Oil & Chemicals Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Granville Oil & Chemicals Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.