

**Floor Paint - Grey**

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) &amp; 2020/878

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product Name Floor Paint - Grey  
Product code 3001  
Unique Formula Identifier (UFI) H750-R0T3-000R-RM5R

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified Use(s) PC9a Coatings and paints, thinners, paint removers  
Uses Advised Against Not known.

**1.3 Details of the supplier of the safety data sheet**

Manufacturer  
Company Identification Granville Oil & Chemicals Ltd  
Address of Manufacturer 29 Goldthorpe Ind. Est.,  
Goldthorpe,  
Rotherham,  
South Yorkshire,  
Postal code S63 9BL  
Telephone: +44 (0)1709 890099  
Fax Not known.  
E-mail lab@granvilleoil.com  
Office hours 08:00 - 17:00  
Responsible Person  
Company Identification Veedol Deutschland GmbH  
Address of Responsible Person Hans-Böckler-Straße 10  
Langenfeld,  
Germany

Postal code 40764  
Telephone: +49 (0) 2173 893 30 30  
Fax Not known.  
E-mail lab@granvilleoil.com  
Office hours

**1.4 Emergency telephone number**

Emergency Phone No. +44 (0)1709 890099  
Contact Granville Lab  
National response centre  
Address NHS Direct  
Emergency Phone No. +44 111

**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture**

Regulation (EC) No. 1272/2008 (CLP) Flam. Liq. 3 :Flammable liquid and vapour.  
Skin Sens. 1A :May cause an allergic skin reaction.

**Floor Paint - Grey**

STOT SE 3 :May cause drowsiness or dizziness.

STOT RE 1 :Causes damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3 :Harmful to aquatic life with long lasting effects.

**2.2 Label elements**

According to Regulation (EC) No. 1272/2008 (CLP)

Product Name

Floor Paint - Grey

Contains

HYDROCARBONS, C9-C11, n-ALKANES, ISOALKANES, CYCLICS,

Hazard Pictogram(s)



GHS02



GHS08



GHS07

Signal Word(s)

Danger

Hazard Statement(s)

H226: Flammable liquid and vapour.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed.

Do not breathe spray or mist.

Precautionary Statement(s)

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents in accordance with local, state or national legislation.

Unique Formula Identifier (UFI)

H750-R0T3-000R-RM5R

**2.3 Other hazards**

None known.

**2.4 Additional Information**

For full text of H/P Statements see section 16.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.1 Substances**

**Floor Paint - Grey**

Not applicable.

**3.2 Mixtures**

| HAZARDOUS INGREDIENT(S)   | CAS No.    | EC No. / REACH Registration No. | %W/W  | Hazard Statement(s)   | Hazard Pictogram(s)              |
|---|------------|---------------------------------|-------|---|----------------------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics     | 64742-48-9 | 919-857-5                       | 10-30 | Flam. Liq. 3 H226<br>Asp. Tox. 1 H304<br>STOT SE 3 H336   | GHS02<br>GHS08<br>GHS07          |
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | 64742-82-1 | 919-446-0                       | 10-30 | Flam. Liq. 3 H226<br>Asp. Tox. 1 H304<br>STOT SE 3 H336<br>STOT RE 1 H372<br>Aquatic Chronic 2 H411         | GHS02<br>GHS08<br>GHS07<br>GHS09 |
| cobalt bis(2-ethylhexanoate)  | 136-52-7   | 205-250-6                       | <0.3  | Skin Sens. 1A H317<br>Eye Irrit. 2 H319<br>Repr. 1B H360F<br>Aquatic Acute 1 H400<br>Aquatic Chronic 3 H412 | GHS08<br>GHS07<br>GHS09          |

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures**

|              |  |
|--------------|--|
| Inhalation   | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues                                       |
| Skin Contact | Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing. |
| Eye Contact  | Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.                          |
| Ingestion    | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.                                      |

**4.2 Most important symptoms and effects, both acute and delayed**

No data available on the mixture itself.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: FIREFIGHTING MEASURES**



## Floor Paint - Grey

### 5.1 Extinguishing media

Suitable Extinguishing media      Extinguish with alcohol-resistant foam, carbon dioxide or dry powder. Do not use water, if avoidable.

Unsuitable extinguishing media      Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### 5.3 Advice for firefighters

Cool containers exposed to flames with water until well after the fire is out. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing, gloves, eye and face protection.

### 6.2 Environmental precautions

Avoid the spillage or runoff entering drains, sewers, or watercourses.

### 6.3 Methods and material for containment and cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing, or apron, as appropriate. Absorb small quantities with paper towels and evaporate in a safe place. Flush spilled material into suitable retaining areas or container with large quantities of water.

### 6.4 Reference to other sections

See Also Section 8, 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid spilling. Keep away from heat, sparks and open flame. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Storage temperature

Ambient.

Storage life

Stable under normal conditions.

Incompatible materials

None known.

### 7.3 Specific end use(s)

PC9a Coatings and paints, thinners, paint removers

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

**Floor Paint - Grey**

8.1.1 Occupational Exposure Limits No Occupational Exposure Limit assigned.

**8.2 Exposure controls**

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Use with ventilation, local exhaust ventilation or breathing protection. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection Wear eye protection (EN166). Personal protective equipment that provides appropriate eye and face protection should be worn.



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Check that the respirator fits tightly, and the filter is changed regularly.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

|  |  |
|--|--|
| Physical state   | Viscous Liquid.  |
| Colour   | Grey.  |
| Odour  | Characteristic.  |
| Melting point/freezing point                             | Not known.   |
| Boiling point or initial boiling point and boiling range | Approx. 158° C   |
| Flammability   | Not known.   |
| Lower and upper explosion limit                          | Lower flammable/explosive limit: 0.7% Upper flammable/explosive limit: 7%.     |
| Flash Point  | 38° C Closed cup.  |
| Auto-ignition temperature                                | Not known.   |
| Decomposition Temperature                                | Not known.   |
| pH   | Not known.   |
| Kinematic Viscosity                                      | >20.5 mm <sup>2</sup> /s   |
| Solubility   | Solubility (Water) : Immiscible with water.<br>Solubility (Other) : Not known. |
| Partition coefficient n-octanol/water (log value)        | Not known.   |
| Vapour pressure  | Not known.   |
| Density and/or relative density                          | 1.00 - 1.20.   |
| Relative vapour density                                  | Not known.   |

**Floor Paint - Grey**

Particle characteristics Not known.

**9.2 Other information**

None.

**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity**

None anticipated.

**10.2 Chemical Stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

No hazardous reactions known if used for its intended purpose.

**10.4 Conditions to avoid**

Avoid heat, flames, and other sources of ignition.

**10.5 Incompatible materials**

Strong bases Oxidising agents.

**10.6 Hazardous decomposition products**

Fire creates: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

|                                |  |
|--------------------------------|--|
| Acute toxicity - Ingestion     | Calculation method : Not classified.   |
| Acute toxicity - Skin Contact  | Calculation method : Not classified.   |
| Acute toxicity - Inhalation    | Calculation method : Not classified.   |
| Skin corrosion/irritation      | Calculation method : Not classified.   |
| Serious eye damage/irritation  | Calculation method : Not classified.   |
| Skin sensitization data        | Calculation method : May cause an allergic skin reaction.                            |
| Respiratory sensitization data | Calculation method : Not classified.   |
| Germ cell mutagenicity         | Calculation method : Not classified.   |
| Carcinogenicity                | Calculation method : Not classified.   |
| Reproductive toxicity          | Calculation method : Not classified.   |
| Lactation                      | Calculation method : Not classified.   |
| STOT - single exposure         | Calculation method : May cause drowsiness or dizziness.                              |
| STOT - repeated exposure       | Calculation method : Causes damage to organs through prolonged or repeated exposure. |
| Aspiration hazard              | Calculation method : Not classified.   |

**11.2 Information on other hazards**

Not known.

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity**

**Floor Paint - Grey**

|  |  |
|--|--|
|  | Harmful to aquatic life with long lasting effects. |
| Toxicity - Aquatic invertebrates               | Not known.   |
| Toxicity - Fish                                | Not known.   |
| Toxicity - Algae                               | Not known.   |
| Toxicity - Sediment Compartment                | Not classified.                                    |
| Toxicity - Terrestrial Compartment             | Not classified.                                    |
| <b>12.2 Persistence and degradability</b>      |  |
|  | Not known.   |
| <b>12.3 Bioaccumulative potential</b>          |  |
|  | Not known.   |
| <b>12.4 Mobility in soil</b>                   |  |
|  | Not known.   |
| <b>12.5 Results of PBT and vPvB assessment</b> |  |
|  | Not known.   |
| <b>12.6 Endocrine disrupting properties</b>    |  |
|  | None known.  |
| <b>12.7 Other adverse effects</b>              |  |
|  | Not known.   |

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

The generation of waste should be minimised or avoided wherever possible.  
Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**13.2 Additional Information**

Disposal should be in accordance with local, state or national legislation.

**SECTION 14: TRANSPORT INFORMATION****14.1 UN number or ID number**

UN No. 1263

**14.2 UN proper shipping name**

UN proper shipping name PAINT

**14.3 Transport hazard class(es)**

ADR/RID

ADR/RID Class 3

ADR Classification Code F1

Special Provisions 163, 367, 650

Limited Quantities 5 L

Excepted Quantities E1

Emergency Action Code •3Y

Mixed Packing Instructions for Packages P001 IBC03 LP01 R001

**Floor Paint - Grey**

|  |                      |
|--|----------------------|
| Special Packing Provisions for Packages                              | PP1                  |
| Mixed Packing Instructions for Packages                              | MP19                 |
| Packing Instructions for Portable Tanks                              | T2                   |
| Special Provisions for Portable Tanks                                | TP1 TP29             |
| Tank Code for Tanks  | LGBF                 |
| Special Provisions for Tanks   |                      |
| Vehicle for Tank Carriage  | FL                   |
| ADR Transport Category   | 3                    |
| Tunnel Restriction Code  | D/E                  |
| Special Provisions for Carriage - Packages                           | V12                  |
| Special Provisions for Carriage - Bulk                               |                      |
| Special Provisions for Carriage - Loading, Unloading and Handling    |                      |
| Special Provisions for Carriage - Operation                          | S2                   |
| ADR HIN  | 30                   |
| IMDG   |                      |
| IMDG Class   | 3                    |
| Special Provisions   | 163, 367, 650        |
| Limited Quantities   | 5 L                  |
| Excepted Quantities  | E1                   |
| Mixed Packing Instructions for Packages                              | P001 IBC03 LP01 R001 |
| Special Packing Provisions for Packages                              | PP1                  |
| Packing Instructions for Portable Tanks                              | T2                   |
| Special Provisions for Portable Tanks                                | TP1 TP29             |
| IMDG EMS   | F-E, S-E             |
| Stowage and Handling Segregation                                     | Category A           |
| Marine Pollutant   |                      |
| ICAO/IATA  |                      |
| IATA Proper Shipping Name  | PAINT                |
| Excepted Quantities  | E1                   |
| Passenger and Cargo Aircraft Limited Quantities Packing Instructions | Y344                 |
| Passenger and Cargo Aircraft Limited Quantities Max net Qty          | 10L                  |
| Passenger and Cargo Aircraft Packing Instructions                    | 355                  |
| Passenger and Cargo Aircraft Max net Qty                             | 60L                  |
| Cargo Aircraft Packing Instructions                                  | 366                  |
| Cargo Aircraft Max net Qty   | 220L                 |



**Floor Paint - Grey**

Special Provisions A3, A72, A192  
Emergency Response Guidebook (ERG) 3L  
Code  
Labels  
Labels 3

**14.4 Packing group**

Packing group III

**14.5 Environmental hazards**

Environmental hazards Not classified as a Marine Pollutant.

**14.6 Special precautions for user**

Special precautions for user Not known.

**14.7 Maritime transport in bulk according to IMO instruments**

No information available

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very High Concern for Authorisation Not listed

REACH: ANNEX XIV list of substances subject to authorisation Not listed

REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Mutagens: category 1B (64742-48-9), Mutagens: category 1B (64742-82-1), cobalt bis(2-ethylhexanoate) (136-52-7)

Community Rolling Action Plan (CoRAP) Not listed

Regulation (EU) N° 2019/1021 of the European Parliament and of the Council on persistent organic pollutants Not listed

Regulation (EC) N° 1005/2009 on substances that deplete the ozone layer Not listed

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Not listed

**National regulations**

Other Not known.

**15.2 Chemical Safety Assessment**

A REACH chemical safety assessment has not been carried out.

**SECTION 16: OTHER INFORMATION**

**Floor Paint - Grey**

The following sections contain revisions or new statements:

**LEGEND**

Hazard Pictogram(s)



GHS02



GHS08



GHS07

GHS09: GHS: Environment

Hazard classification

Flam. Liq. 3 : Flammable liquid, Category 3  
Asp. Tox. 1 : Aspiration hazard, Category 1  
Skin Sens. 1A : Skin sensitization, Category 1A  
Eye Irrit. 2 : Serious eye damage/irritation, Category 2  
STOT SE 3 : Specific target organ toxicity — single exposure, Category 3  
Repr. 1B : Reproductive toxicity, Category 1B  
STOT RE 1 : Specific target organ toxicity — repeated exposure, Category 1  
Aquatic Acute 1 : Hazardous to the aquatic environment, Acute, Category 1  
Aquatic Chronic 2 : Hazardous to the aquatic environment, Chronic, Category 2  
Aquatic Chronic 3 : Hazardous to the aquatic environment, Chronic, Category 3

Hazard Statement(s)

H226: Flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H360F: May damage fertility.  
H372: Causes damage to organs through prolonged or repeated exposure.  
H400: Very toxic to aquatic life.  
H411: Toxic to aquatic life with long lasting effects.  
H412: Harmful to aquatic life with long lasting effects.  
EUH211: Warning! Hazardous respirable droplets may be formed when sprayed.  
Do not breathe spray or mist.

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233: Keep container tightly closed.  
P240: Ground and bond container and receiving equipment.

**Floor Paint - Grey**

P241: Use explosion-proof electrical/ventilating/lighting/equipment.  
P242: Use non-sparking tools.  
P243: Take action to prevent static discharges.  
P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264: Wash hands and exposed skin thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312: Call a POISON CENTRE/doctor if you feel unwell.  
P314: Get medical advice/attention if you feel unwell.  
P321: Specific treatment (see Medical Advice on this label).  
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364: Take off contaminated clothing and wash it before reuse.  
P370+P378: In case of fire: Use water spray, dry powder or carbon dioxide to extinguish.  
P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
P403+P235: Store in a well-ventilated place. Keep cool.  
P405: Store locked up.  
P501: Dispose of contents in accordance with local, state or national legislation.

## Acronyms

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE : Acute Toxicity Estimate  
CAS : Chemical Abstracts Service  
CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures  
DNEL : Derived No Effect Level  
EC : European Community  
EINECS : European Inventory of Existing Commercial Chemical Substances  
IATA : International Air Transport Association  
IBC : Intermediate Bulk Container  
ICAO : International Civil Aviation Organization  
IMDG : International Maritime Dangerous Goods

**Floor Paint - Grey**

LTEL : Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources  
for data used to compile the SDS

Regulation (EC) No. 1272/2008 (CLP)

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Granville Oil & Chemicals Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Granville Oil & Chemicals Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.