

Granville FS Motorsport 10W/60

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Granville FS Motorsport 10W/60 uses synthetic additive technology designed to provide optimum performance and protect under the most severe driving conditions. Suitable for use in high performance, competition and modified engines both normally aspirated and turbo charged.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SM/CF

ACEA: A3/B4

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|---------|---------|---------------|
| 1 Litre | 0488 | 5020618004882 |
| 5 Litre | 0489 | 5020618004899 |



Granville FS Motorsport 10W/60

1 Litre & 5 Litre

Odour : Characteristic

Solubility : Insoluble in water

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 21.9 | <26.1 | 24.396 |
| Viscosity, CCS -25°C | ASTM D4684 | mPa.s | | 7000 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 10 | | 10.625 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.7 | | |
| NOACK Volatility | ASTM D5800 | % | | 13 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 168.124 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |
| Pour Point | ASTM D97 | °C | | -30 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

