

# Granville Diesel Gold 15W/40

5 Litre

## PRODUCT DESCRIPTION

Granville Diesel Gold 15W/40 is a semi-synthetic engine oil for use in older engines requiring a lubricant of this grade.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 505.00 & 502.00

ACEA: A3/B4

API: SN/CF

MB: 229.3



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

## PRODUCT USAGE

For engines where this specification lubricant is required.

## DIRECTIONS FOR USE

As recommended by the engine manufacturer.

## STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

## SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble

SIZE	PART NO	BARCODE
5 Litre	0880	5020618008804



# Granville Diesel Gold 15W/40

5 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	12.5	<16.3	
Viscosity Index	ASTM D2270		80		
Viscosity, CCS -20°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		
Pour Point	ASTM D97	°c		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

