

## Granville ATF Dexron III

1 Litre, 5 Litre, 20 Litre & 205 Litre

### PRODUCT DESCRIPTION

Granville ATF Dexron III is a synthetic based multi-purpose automatic transmission fluid for automatic gearboxes. ATF Dexron III is formulated using the very latest additive technology to give a product that is frictionally stable as well as giving extended service even under the most testing of conditions.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

GM: Dexron II & Dexron III  
 Ford: Mercon&#174;, WSS-M2C138-J & WSS-M2C166-H  
 Allison: C4  
 MB: 236.5 & 236.9  
 ZF: TE-ML-09, TE-ML-11 & TE-ML-14

### PRODUCT BENEFITS

- \* Semi synthetic
- \* Extended service life
- \* Excellent protection & stability

### PRODUCT USAGE

Granville ATF Dexron III is designed for use in automatic transmissions manufactured by General Motors, Vauxhall and Opel to name but a few. It may also be used in other manufacturer's vehicles where recommended and as a power steering fluid where recommended.

### DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	0224	5020618002246
5 Litre	0225	5020618002253
20 Litre	0090	5020618000907
205 Litre	0229	5020618002291



# Granville ATF Dexron III

1 Litre, 5 Litre, 20 Litre & 205 Litre

## STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

## SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	:	Red liquid
<b>Odour</b>	:	Characteristic
<b>Solubility</b>	:	Insoluble in water
<b>Percentage of Base Oil</b>	:	Less than 70%
<b>Percentage of Biodiesel</b>	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s			7.55
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			37.26
Density	ASTM D792	@ 15°C			0.848

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

