

Granville EpeX 80/90

1 Litre, 5 Litre, 20 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville EPEX 80/90 is a multi-grade extreme pressure gear oil formulated for use in heavy duty, high load applications. The formulation provides a gear oil with outstanding anti wear protection. EPEX 80/90 is designed to cope with the increasing demands of modern day motoring which include high shock/load, high torque and high speeds.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5
 MIL: MIL-L-2105 B, MIL-L-2105 C & MIL-L-2105 D
 MAN: 342-Type M1 & 342-Type M2
 Scania: STO 1.0
 Volvo: 1273.10
 ZF: TE-ML-05A, TE-ML-07A, TE-ML-08, TE-ML-12E, TE-ML-16B, TE-ML-16C, TE-ML-16D, TE-ML-17B, TE-ML-19B & TE-ML-21A

PRODUCT BENEFITS

- * Excellent high & low temperature performance
- * Outstanding protection against corrosion
- * Suitable for synchromesh gearboxes
- * Can be used where EP 80, EP 90 and GL4 specifications are also required

PRODUCT USAGE

For manual transmissions and axles where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 1 Litre | 0143 | 5020618001430 |
| 5 Litre | 0173 | 5020618001737 |
| 20 Litre | 0137 | 5020618001379 |
| 205 Litre | 1486 | 5020618014867 |



Granville Epex 80/90

1 Litre, 5 Litre, 20 Litre & 205 Litre

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

| | | |
|--------------------------------|---|--------------------|
| Appearance | : | Amber liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|-----------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 13.5 | <18.5 | 16.087 |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 151.27 |
| Density | ASTM D792 | @ 15°C | | | 0.8932 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

