

TECHNICAL DATA

Granville LS 80W/90

1Litre & 5 Litre

PRODUCT DESCRIPTION

Granville LS 80W/90 is a specially formulated extreme pressure gear oil for optimum performance of limited slip differentials. LS 80W/90 is a blend of high quality base oils, performance EP additives and specially selected friction modifiers to provide a lubricant with exacting requirements for limited slip operations.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5

PRODUCT BENEFITS

- * Reduces whining and chattering
- * Ensures clutch plates slide smoothly
- * Outstanding extremes of temperature protection

* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1Litre	1636	5020618016366
5 Litre	1715	5020618017158

PRODUCT USAGE

Suitable for limited slip differentials fitted to cars, vans, trucks, buses and agricultural equipment.

DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.

STORAGE INSTRUCTIONS

As recommended by the vehicle manufacturer.

SHELF LIFE

5 years from date of manufacture.

Revision: 3 | Date: 11/11/2016

Appearance : Amber liquid





TECHNICAL DATA

Granville LS 80W/90

1 Litre & 5 Litre

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Base Oil : More Than 70%

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	13.5	<18.5	15.98
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			153.42
Density	ASTM D792	@ 15°c			0.893

SAFETY PRECAUTIONS

Revision: 3 | Date: 11/11/2016

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

