

## Granville EP 85W/140

1 Litre, 5 Litre & 20 Litre

### PRODUCT DESCRIPTION

Granville EP 85W/140 is a multigrade gear oil for heavy duty applications that has been formulated using a blend of quality base oils, the latest additive technology and extreme pressure additives to provide a gear oil that operates under the most severe of conditions.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-5  
 MIL: MIL-L-2105 B, MIL-L-2105 C & MIL-L-2105 D  
 MAN: 342-Type M1 & 342-Type M2  
 ZF: TE-ML-05A, TE-ML-07A, TE-ML-08, TE-ML-12E, TE-ML-16B, TE-ML-16C, TE-ML-16D, TE-ML-17B, TE-ML-19B & TE-ML-21A

### PRODUCT BENEFITS

- \* Outstanding temperature control
- \* Excellent anti corrosion properties
- \* For heavy duty applications

### PRODUCT USAGE

For manual gearboxes and axles where heavy duty service applications are required.

### DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.

### STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1637	5020618016373
5 Litre	1716	5020618017165
20 Litre	1714	5020618017141



# Granville EP 85W/140

1 Litre, 5 Litre & 20 Litre

## SHELF LIFE

5 years from date of manufacture.

## SPECIFICATION INFORMATION

API: GL5  
MIL-L-2105B/C/D

**Appearance** : Amber liquid  
**Odour** : Characteristic  
**Solubility** : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	24	<32.5	28.59
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			406.43
Density	ASTM D792	@ 15°C			0.9

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

