Burgess
Marine Clearsealer
500ml, 1 Litre, 2.5 Litre & 5 Litre

PRODUCT DESCRIPTION

Burgess Marine Clearsealer is a UV stable waterborne fine particle acrylic emulsion. When applied to timber, Marine Clearsealer dries to form a microporous membrane, sealing the timber. Marine Clearsealer is ideal for the treatment of wood in areas not subject to direct sunlight. It is specially suited for interior use where minimum colouration is required. Marine Clearsealer is UV stable but unlike Marine Woodsealer it does not contain UV blocking agents that protect the wood therefore, when used on exterior surfaces, it should always be used as a top coat in conjunction with Marine Woodsealer.



* Image for illustrative purposes only.

PRODUCT BENEFITS

* Quick drying
* Water based
* Allows timbers to breathe

SIZE	PART NO	BARCODE
500ml	0730	5020618007302
1 Litre	0731	5020618007319
2.5 Litre	0732	5020618007326
5 Litre	0733	5020618007333

PRODUCT USAGE

Marine Clearsealer is ideal for the treatment of wood in areas not subject to direct sunlight. It is specially suited for interior use where minimum colouration is required.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Burgess
Marine Clearsealer

500ml, 1 Litre, 2.5 Litre & 5 Litre

DIRECTIONS FOR USE

Burgess Marine Clearsealer can be applied by brush, spray or soft cloth. It is recommended to apply a minimum of two coats however, on very porous timber, more coats may be required. Marine Clearsealer will normally dry in 15 minutes. Additional coats may be applied before the product has dried.
An air temperature of 5°C - 30°C is preferred but avoid applying the product if the relative humidity is greater than 80%. Avoid applying when there is a risk of rain or heavy condensation during the drying period. When applying in confined spaces ensure sufficient air movement is available to remove excess moisture released during the drying process. Clean all brushes and spray equipment with clean water before the product dries.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

SHELF LIFE

2 years from date of manufacture if stored unopened in the original container in a frost-free environment.

SPECIFICATION INFORMATION

Touch dry: 15 minutes
Coverage: 8m^2/l (dependent upon absorbency of substrate)

Appearance	:	Milky off white solution
Odour	:	Mild perceptible odour
Specific Gravity	:	1.04
Solubility	:	Miscible in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com