

TECHNICAL DATA

Burgess Marine Top Gloss

500ml, 1 Litre, 2.5 Litre & 5 Litre

PRODUCT DESCRIPTION

Burgess Marine Top Gloss is formulated from similar, but harder, resins to those used in Woodsealer. This gives a crystal clear gloss finish if applied over the matt finish of Woodsealer. Burgess Marine Top Gloss is ultra violet stable but does not have UV blockers and so for exteriors should be used over the top of Marine Woodsealer.

PRODUCT BENEFITS

- * Crystal clear gloss finish
- * Ultra Violet stable
- * For interior and exterior use



* Image for illustrative purposes only.

PRODUCT USAGE

For use as a Top Gloss coating over Burgess Woodsealer & Clearsealer

DIRECTIONS FOR USE

Revision: 2 | Date: 04/05/2012

For internal use Top Gloss must be applied to clean, dry wood. For external use or surfaces exposed to sunlight always use Burgess Marine Woodsealer as a primer before applying Top Gloss. Top Gloss dries very quickly. Air bubbles may not have time to escape and become trapped. To avoid this use a good quality soft dense brush or lint free cloth. Apply thin coats with minimum brushwork. (In hot conditions it may be beneficial to dilute Top Gloss with water, about 10% by volume, to slow down drying time). A second coat can be applied after 30 minutes if drying conditions are good (low humidity, temperature above 10°C and well ventilated). Allow to cure for 24 hours before exposing to moisture. If the wood surface is not dry before applying Top Gloss or the surface is wetted before fully cured, Top Gloss will 'bleach' ie. turn milky. Do not despair, unlike blooming in solvent based varnishes, when conditions permit Top Gloss will dry to a clear finish. Clean brushes, spills etc. with water before the product dries. Use petrol or thinners to remove dry spots.

SIZE	PART NO	BARCODE
500ml	0744	5020618007449
1 Litre	0745	5020618007456
2.5 Litre	0746	5020618007463
5 Litre	0747	5020618007470





TECHNICAL DATA

Burgess Marine Top Gloss

500ml, 1 Litre, 2.5 Litre & 5 Litre

STORAGE INSTRUCTIONS

Store in a cool, dry place and protect from frost.

SHELF LIFE

24 months from date of manufacture.

Appearance : Milky off-white liquid

Odour : Characteristic

Solubility : Soluble in water

Flammability : Non - flammable

SAFETY PRECAUTIONS

Revision: 2 | Date: 04/05/2012

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

