

Granville Hypalube C3 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube C3 fully synthetic engine oil has been specially formulated to meet the requirements of a Low SAPS (Sulphated Ash, Phosphorus and Sulphur) engine oil. Hypalube C3 is suitable for use in vehicles fitted with exhaust after treatment devices that recommend a lubricant of the grade and specification

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
API: SN/CF
BMW: LL-04
GM: Dexos™ 2
MB: 229.31, 229.51 & 229.52
VW: 505.00 & 505.01
Opel: OV0401547-D30

PRODUCT BENEFITS

- * Fully Synthetic Formulation
- * Long Life capabilities
- * Protects engine at optimum temperature and performance
- * For use with exhaust after treatment devices

PRODUCT USAGE

Use as per the engine manufacturers recommendations

DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 1 Litre | 0526 | 5020618005261 |
| 5 Litre | 0527 | 5020618005278 |
| 20 Litre | 0564 | 5020618005643 |
| 199 Litre | 0529 | 5020618005292 |



Granville Hypalube C3 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture.

| | |
|-------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 12.3 |
| Viscosity, CCS -30°C | ASTM D4684 | mPa.s | | 6600 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 7 | | 7.98 |
| Pour Point | ASTM D97 | °C | | -36 | |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.5 | | |
| NOACK Volatility | ASTM D5800 | % | | 10 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 73.3 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

