Granville®
More than just an oil company

TECHNICAL DATA

Revision: 3 | Date: 26/01/2017

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville

Hypalube C4 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville Hypalube C4 5W/30 is an advanced, fully synthetic low viscosity engine oil formulated to meet the performance demands required by manufacturers who recommend an oil that combines high performance, fuel efficiency and emission control. Manufactured to a Low SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C4 oil.
It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C4
MB: 226.51
Renault: RN0720

SIZE	PART NO	BARCODE
1 Litre	0814	5020618008149
5 Litre	0815	5020618008156
20 Litre	0819	5020618008194
199 Litre	0818	5020618008187

PRODUCT BENEFITS

* Low SAPS (Sulphated ash, phosphorous and sulphur content) formulation
* Fully Synrthetic

PRODUCT USAGE

Use where recommended by the engine manufacturer

DIRECTIONS FOR USE

Use as required by the engine manufacturer

STORAGE INSTRUCTIONS

Store sealed and pright in a cool dry place out of the reach of children

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville

Hypalube C4 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	12.3
Viscosity, CCS -30°c	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.4
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			74.4
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				164

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com