

# TECHNICAL DATA

# Granville ATF LG6

1 Litre, 5 Litre & 20 Litre

## PRODUCT DESCRIPTION

Fully synthetic, premium quality transmission fluid formulated for the specific requirements of ZF 6/8/9 speed transmissions. ATF LG6 is formulated to be extremely shear stable providing advanced protection and performance that is required for fuel efficient 6+ speed transmissions.

# RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ATF: M-1375.6 & M-1375.8 BMW/Mini: 83 22 2 152 426 Chrysler: 68157995A Jaguar: 02JDE26444 Land Rover: LR23288 Mazda: ATF-FZ

MB: 236.15 VW: G 060 162

ZF: Lifeguard 6+, Lifeguard 8 & Lifeguard 9



\* Image for illustrative purposes only.

| SIZE     | PART NO | BARCODE       |
|----------|---------|---------------|
| 1 Litre  | 1595    | 5020618015956 |
| 5 Litre  | 1596    | 5020618015963 |
| 20 Litre | 1593    | 5020618015932 |

#### **PRODUCT BENEFITS**

- \* Shear stable
- \* Quality, fully synthetic formulation
- \* Offers excellent protection against heat build up and component wear

#### PRODUCT USAGE

For use in ZF 6/8/9 speed automatic transmissions

## **DIRECTIONS FOR USE**

Revision: 5 | Date: 07/02/2018

Use as per the transmission manufacturers recommendations





# TECHNICAL DATA

# Granville ATF LG6

1 Litre, 5 Litre & 20 Litre

# STORAGE INSTRUCTIONS

Store upright and sealed in a cool dry place out of the reach of children

## SHELF LIFE

5 years from date of manufacture

#### SPECIFICATION INFORMATION

Suitable for use in vehicles that require the following specifications: ATF M-1375.6, ATF M-1375.8, BMW:83222152426, Chrysler: 68157995A, Jaguar: 02JDE26444, Land Rover: LR023288, Mazda: ATF-FZ, MB: 236.15. VAG: G 060 162 A1/A2/A6, 090 252/3/5, ZF Lifeguard 6+/8

Appearance : Green liquid

Odour : Characteristic

Solubility : Insoluble in water

Flammability : >200°C

Revision: 5 | Date: 07/02/2018





# TECHNICAL DATA

# Granville ATF LG6

1 Litre, 5 Litre & 20 Litre

| Test                       | Method    | Unit   | Min. | Max. | Typical |
|----------------------------|-----------|--------|------|------|---------|
| Viscosity, Kinematic 100°c | ASTM D445 | mm²/s  |      |      | 6.2     |
| Viscosity, Kinematic 40°c  | ASTM D445 | mm²/s  |      |      | 36      |
| Density                    | ASTM D792 | @ 15°c |      |      | 0.848   |

### **SAFETY PRECAUTIONS**

Revision: 5 | Date: 07/02/2018

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

