

# Granville MTF FS 75W/80

1 Litre

## PRODUCT DESCRIPTION

MTF- FS 75W/80 is a high quality fully synthetic manual transmission fluid, formulated to protect the synchronisers in modern manual transmissions. It offers superior gear shift capabilities and fuel efficiency using selected additives to ensure good low temperature performance, bearing and gear protection and fuel efficiency.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-4  
GM: 1940768  
Volvo: 97308  
Ford: ESD-M2C186-A  
BMW: MTF LT-2  
Honda: Special MTF & Special MTF-II  
MTF: 94  
VW: G 055 512



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1586	5020618015864

## PRODUCT BENEFITS

- \* Protects synchronisers from wear
- \* Ensures positive gear selection
- \* Fully synthetic

## DIRECTIONS FOR USE

Use as per the manufacturers recommendations

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place away from the reach of children



# Granville MTF FS 75W/80

1 Litre

## SHELF LIFE

5 years from date of manufacture

## SPECIFICATION INFORMATION

Suitable for use in manual transmissions where the following specifications are required

API: GL-4, BMW: MTF LT-2, Honda Special MTF/MTF II, GM: 1940768, MTF 94, Ford: M2C186-A. Volvo: 97308

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Flammability</b>	: >200°C

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	7	<11	10.01
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			56.91
Density	ASTM D792	@ 15°C			0.85

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

