

Granville MTF FS 75W/90

1 Litre, 5 Litre & 20 Litre

PRODUCT DESCRIPTION

Granville MTF FS 75W/90 is a fully synthetic manual transmission fluid developed to protect and maintain synchroniser performance. The formulation gives enhanced gear shift capabilities and fuel efficiency by controlling friction and heat build up within the transmission.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-4

GM: 1940768, 1940182 & 1940764

Ford: WSD-M2C200-B & WSD-M2C200-C

VW: G 50

Volvo: 97309



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Fully synthetic
- * Maintains synchroniser performance
- * Controls friction and heat build up

PRODUCT USAGE

Use as per the vehicle manufacturers recommendations

STORAGE INSTRUCTIONS

Store upright and sealed in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

| SIZE | PART NO | BARCODE |
|----------|---------|---------------|
| 1 Litre | 1577 | 5020618015772 |
| 5 Litre | 1578 | 5020618015789 |
| 20 Litre | 1579 | 5020618015796 |



Granville MTF FS 75W/90

1 Litre, 5 Litre & 20 Litre

SPECIFICATION INFORMATION

Suitable for use in manual transmission where the following specifications are recommended:

API: GL-4, Ford: WSD-M2C200-B/C, GM:1940768, GM:1940182, GM:1940764, Volvo: 97309, VAG: G50

| | |
|-------------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |
| Flammability | : >200°C |
| Percentage of Base Oil | : Less than 70% |
| Percentage of Biodiesel | : Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|-----------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 13.5 | <18.5 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

