



# Granville

## MTF FS 75W

1 Litre & 5 Litre

### PRODUCT DESCRIPTION

Granville MTF FS 75W is a quality fully synthetic manual transmission fluid that protects synchronisers in modern manual transmissions. It offers superior gear shift capabilities under severe conditions whilst giving the added benefit of being fuel efficient. Using selected additives ensures good low temperature performance, bearing and gear protection and fuel efficiency.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: GL-4  
VW: G 052 512, G 052 178, G 060 726, G 052 171 & G 055 512  
BMW: MTF LT-3  
Ford: WSS-M2C200-D2  
PSA: B71 2316

### PRODUCT BENEFITS

- \* Superior gear shift
- \* Effective under severe conditions
- \* Fuel efficient

### DIRECTIONS FOR USE

Use as per the vehicle manufacturers recommendations

### STORAGE INSTRUCTIONS

Store upright and sealed in a cool dry place out of the reach of children

### SHELF LIFE

5 years from date of manufacture



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1410	5020618014102
5 Litre	1411	5020618014119



## Granville

# MTF FS 75W

1 Litre & 5 Litre

### SPECIFICATION INFORMATION

Suitable for use in manual transmissions where the following specifications are required

API: GL-4, BMW: MTF LT-3, Ford: WSS-M2C200-D2, VW: G 052 178, G 060 726, G 052 171, G 052 726 & G 052 512

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Flammability</b>	: >200°C

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	7	<11	10.01
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			56.91
Density	ASTM D792	@ 15°C			0.85

### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

