

Granville Running In Oil

5 Litre

PRODUCT DESCRIPTION

Running In Oil is low detergent, non friction modified oil specially formulated to promote the bedding in of newly machined mated surfaces in re-built engines. High quality additives overcome bore glazing allowing accurate seating of the piston rings and valves. Can be used for up to 1000 miles of normal road use.

PRODUCT BENEFITS

- * Non detergent oil
- * Ensures correct bedding in of newly machined mated surfaces
- * Eliminates bore glaze

PRODUCT USAGE

For limited use in newly re-built petrol and diesel engines which can be used for up to 1000 miles of normal road use. Ideal for use in engine on test benches.

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.

SHELF LIFE

5 years from date of manufacture

- | | | |
|-------------------|---|--------------------|
| Appearance | : | Amber liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
5 Litre	1821	5020618018216



Granville Running In Oil

5 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.57
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			89.87
Density	ASTM D792	@ 15°C			0.876
Total Base Number	ASTM D2896	mg KOH/g			6.22
Viscosity Index	ASTM D2270		75		
Pour Point	ASTM D97	°C		-15	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

