

Granville Running In Oil

5 Litre

PRODUCT DESCRIPTION

Running In Oil is low detergent, non friction modified oil specially formulated to promote the bedding in of newly machined mated surfaces in re-built engines. High quality additives overcome bore glazing allowing accurate seating of the piston rings and valves. Can be used for up to 1000 miles of normal road use.

PRODUCT BENEFITS

- * Non detergent oil
- * Ensures correct bedding in of newly machined mated surfaces
- * Eliminates bore glaze

PRODUCT USAGE

For limited use in newly re-built petrol and diesel engines which can be used for up to 1000 miles of normal road use. Ideal for use in engine on test benches.



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|---------|---------|---------------|
| 5 Litre | 1821 | 5020618018216 |

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children.

SHELF LIFE

5 years from date of manufacture

Appearance : Amber liquid



Granville Running In Oil

5 Litre

Odour : Characteristic
Solubility : Insoluble in water

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 10.57 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 2.9 | | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 89.87 |
| Density | ASTM D792 | @ 15°C | | | 0.876 |
| Total Base Number | ASTM D2896 | mg KOH/g | | | 6.22 |
| Viscosity Index | ASTM D2270 | | 75 | | |
| Pour Point | ASTM D97 | °C | | -15 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

