

Veedol Sintron C3 5W/30

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Veedol Sintron C3 5W-30 is a universal, synthetic, fuel economy motor oil developed according to the most recent technology. Formulated using specially selected synthetic base oils with high viscosity index and a well-balanced choice of advanced additives which helps achieve the following: improved fuel efficiency; high and shear stable viscosity index; excellent low temperature fluidity ensuring easy cold start; effective lubrication at very high temperatures; unique detergent/dispersion additive system ensuring engine cleanliness with negligible sludge; reduced formation of combustion ashes; very strong protection against wear, corrosion and foaming.

Veedol Sintron C3 5W-30 is specially developed for passenger car unit injector diesel engines. Moreover this lubricant is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application range.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	5000	5020618050001
5 Litre	5001	5020618050018

OEM APPROVALS

BMW: LL-04
 MB-Approval: 229.51 & 229.52
 VW: 505.00 & 505.01
 GM: Dexos™ 2

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
 API: SN

PRODUCT BENEFITS

- * OEM Approved product
- * Improved fuel efficiency
- ** Effective lubrication at very high temperatures



Veedol Sintron C3 5W/30

1 Litre & 5 Litre

PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber oily liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	12.195
Total Base Number	ASTM D2896	mg KOH/g	10		
Pour Point	ASTM D97	°C		<-36	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		10	
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			69.55
Density	ASTM D792	@ 15°C			0.85
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.



Veedol Sintron C3 5W/30

1 Litre & 5 Litre

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

