

Veedol Multigrade Super 10W/40

1 Litre & 5 Litre

PRODUCT DESCRIPTION

Veedol Multigrade Super 10W-40 motor oil is based on a combination of high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:
high and stable viscosity index; fast cold start; strong resistance against oxidation; good detergency and dispersion; safe lubrication film at high temperatures; protection against wear, corrosion and foaming.
Veedol Multigrade Super 10W-40 is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.



* Image for illustrative purposes only.

OEM APPROVALS

MB-Approval: 229.1

RECOMMENDED FOR USE BY VEEDOL FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4
API: SL/CF
VW: 502.00 & 505.00

PRODUCT BENEFITS

- * OEM Approved product
- * Good detergency and dispersion
- * Strong protection against wear, corrosion and foaming

PRODUCT USAGE

Recommended for applications where this grade and specification of lubricant is required

SIZE	PART NO	BARCODE
1 Litre	5020	5020618050209
5 Litre	5021	5020618050216



Veedol Multigrade Super 10W/40

1 Litre & 5 Litre

DIRECTIONS FOR USE

Use as per the engine manufacturers handbook

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber oily liquid
Odour	: Characteristic
Specific Gravity	: 0.873
Solubility	: Insoluble in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

