Granville

FS-PX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville FS-PX 0W/30 is a fully synthetic mid-SAPS engine oil specially formulated to meet the very latest specifications and fuel efficiency targets required by Peugeot/Citroen power units including Blue HDi and Pure Tech engine types. Suitable for use in Petrol and Diesel engines where specified.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2
PSA: B71 2312

PRODUCT BENEFITS

* Fully synthetic
* Reduces fuel consumption
* Stable lubricant film at high temperatures
* Suitable for extended oil drain intervals

SIZE	PART NO	BARCODE
1 Litre	0892	5020618008927
5 Litre	0893	5020618008934
20 Litre	0894	5020618008941
199 Litre	0900	5020618009009

PRODUCT USAGE

For use in engines where this viscosity and specification is required including petrol and diesel engines including those fitted with three way catalysts and diesel particulate filters.

DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place out of the reach of children

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
FS-PX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

SHELF LIFE

5 years from date of manufacture

Appearance	:	Clear amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	11
Viscosity, CCS -35°c	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	6		11.5
Pour Point	ASTM D97	°c		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			61.9
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				171

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com