Granville®
More than just an oil company

TECHNICAL DATA

Revision: 3 | Date: 22/03/2024

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville

FS-FX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre



* Image for illustrative purposes only.

PRODUCT DESCRIPTION

Granville FS-FX 0W/30 is a fully synthetic Mid SAPS engine oil specifically formulated to meet the requirements of the new generation Ford Dura Torq engines (2014>).
This Mid SAPS formulation is also suitable for certain Alfa Romeo, Fiat, Hyundai, Jeep, Kia, Suzuki and Toyota engines where specified

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2
Ford: WSS-M2C950-A
Fiat: 9.55535-DS1 & 9.55535-GS1
STJLR: .03.5007
BMW: LL-12 FE

SIZE	PART NO	BARCODE
1 Litre	0865	5020618008651
5 Litre	0866	5020618008668
20 Litre	0867	5020618008675
199 Litre	0872	5020618008729

PRODUCT BENEFITS

* Especially formulated for certain Ford engines
* Mid SAPS formulation
* Excellent wear and corrosion protection
* Superior fuel efficiency

PRODUCT USAGE

For engines fitted with exhaust after treatment devices where this grade and specification is recommended

DIRECTIONS FOR USE

Use as per the vehicle manufacturers recommendations

HIGH PERFORMANCE
PREMIUM QUALITY

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com

Granville
FS-FX 0W/30
1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool dry place, out of the reach of children

SHELF LIFE

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm^2/s	9.3	<12.5	10.6
Viscosity, CCS -35°c	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	7		9.8
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°c	ASTM D445	mm^2/s			60.4
Density	ASTM D792	@ 15°c			0.85
Viscosity Index	ASTM D2270				169

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

HIGH PERFORMANCE
PREMIUM QUALITY

AUTOMOTIVE LUBRICANTS • QUALITY CHEMICALS • PREMIER BRANDS

Granville Oil & Chemicals Ltd.
29 Goldthorpe Ind. Est., Goldthorpe, Rotherham S63 9BL ENGLAND
Tel: +44 (0)1709 890099 • Web: www.granvilleoil.com