

# Granville FS-XC 0W/20

1 Litre, 5 Litre, 20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Granville FS-XC 0W/20 is a highly advanced fully synthetic engine oil formulated to give comprehensive protection and performance under even the most extreme driving conditions as well as offering increased fuel economy and exceptional lubricant fluidity. Suitable for use in petrol and diesel engines both naturally aspirated and turbo charged where the manufacturer recommends this grade and specification of lubricants

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

Volvo: VCC RBS0-2AE

ACEA: C5

STJLR: .03.5006



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

- \*Increased fuel economy
- \*Exceptional lubricant fluidity
- \*Advanced fully synthetic formulation

## DIRECTIONS FOR USE

Use as recommended by engine manufacturer

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool, dry place out of the reach of children

## SHELF LIFE

5 years from date of manufacture

**Appearance** : Amber liquid

SIZE	PART NO	BARCODE
1 Litre	1066	5020618010661
5 Litre	1067	5020618010678
20 Litre	1068	5020618010685
199 Litre	1071	5020618010715



# Granville FS-XC 0W/20

1 Litre, 5 Litre, 20 Litre & 199 Litre

Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	7	<9.3	8.3
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	7.5		9.9
Pour Point	ASTM D97	°C		-48	
HTHS Viscosity	ASTM D4683	mPa.s	2.75	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			42.2
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				177

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

