

Granville

Hypalube VL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube VL 5W/30 is a fully synthetic engine oil formulated to provide outstanding performance levels both in terms of engine cleanliness and fuel economy. The product is recommended by Granville Oil & Chemicals Ltd for use in Volkswagen, Audi, Seat and Skoda engines requiring a VW specification oil. Hypalube VL 5W/30 is fully compatible with exhaust after treatment devices such as diesel particulate filters.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
VW: 504.00 & 507.00
API: SN/CF
BMW: LL-04
MB: 229.51
Porsche: C30

PRODUCT BENEFITS

- * Effective environmental protection
- * Outstanding fuel efficiency
- * Excellent high & low temperature performance
- * Ensures lubricant performance over extended drain intervals

PRODUCT USAGE

VAG engine types.

DIRECTIONS FOR USE

As recommended by the engine manufacturer



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 1 Litre | 1127 | 5020618011279 |
| 5 Litre | 1128 | 5020618011286 |
| 20 Litre | 1129 | 5020618011293 |
| 199 Litre | 1132 | 5020618011323 |



Granville

Hypalube VL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture

| | |
|-------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 12.4 |
| Total Base Number | ASTM D2896 | mg KOH/g | 7 | | 9.7 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 3.5 | | |
| Viscosity, CCS -30°C | ASTM D4684 | mPa.s | | 6600 | |
| Pour Point | ASTM D97 | °C | | -36 | |
| NOACK Volatility | ASTM D5800 | % | | <10 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 76.8 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |
| Viscosity Index | ASTM D2270 | | | | 159 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

