

Granville Hypalube LL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube LL 5W/30 is formulated primarily to meet the GM longlife requirements using the most advanced additive technology to produce a fuel efficient engine oil that has excellent high and low temperature performance and exceptional long term anti wear characteristics. Suitable for use in petrol & diesel engines where specified including Vauxhall, Opel and Saab.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4

API: SL/CF

BMW: LL-01 & LL-98

GM: LL-A-025 & LL-B-025

MB: 229.3

Opel: B-040-2095 & B-040-2098

VW: 505.00 & 502.00



* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 1 Litre | 1121 | 5020618011217 |
| 5 Litre | 1122 | 5020618011224 |
| 20 Litre | 1123 | 5020618011231 |
| 199 Litre | 1126 | 5020618011262 |

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer



Granville Hypalube LL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture

| | |
|-------------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |
| Percentage of Biodiesel | : Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | 9.3 | <12.5 | 12.4 |
| Viscosity, CCS -30°C | ASTM D4684 | mPa.s | | <6600 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 10 | | 11.9 |
| HTHS Viscosity | ASTM D4683 | mPa.s | >3.5 | | |
| NOACK Volatility | ASTM D5800 | % | | 10 | |
| Pour Point | ASTM D97 | °C | | -27 | |
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 77.1 |
| Viscosity Index | ASTM D2270 | | | | 159 |
| Density | ASTM D792 | @ 15°C | | | 0.85 |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

