



# Granville Sub Zero Universal RTU Antifreeze

1 Litre & 5 Li

## PRODUCT DESCRIPTION

Granville Sub Zero Universal Antifreeze is an all year round antifreeze and coolant. The unique formulation enables this product to be mixed with any ethylene glycol based antifreeze. Sub Zero Universal uses OAT additive technology and is free from nitrites, amines, phosphates, borates and silicates and will provide effective protection for 5 years or 150,000 miles (whichever is the sooner).

If this product is mixed with traditional coolant technology it should be assumed that the service life will be that of the traditional coolant.

This product is NOT suitable to be mixed with glycerine based antifreeze.



\* Image for illustrative purposes only.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

- BS: 6580:2010
- CUNA: NC 956-16
- SAE: J1034
- UNE: 26361-88
- ASTM: D3306 & D4985

SIZE	PART NO	BARCODE
1 Litre	2631	5020618026310
5 Litre	2632	5020618026327

## PRODUCT BENEFITS

- \* Longlife protection
- \* Pre-mixed product
- \* Compatible with other Ethylene glycol based antifreeze

## PRODUCT USAGE

The product is a premix and requires no further dilution

## DIRECTIONS FOR USE

Use as recommended by the engine manufacturer



# Granville

## Sub Zero Universal RTU

### Antifreeze

#### STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

1 Litre & 5 Litre

#### SHELF LIFE

5 years from date of manufacture

#### SPECIFICATION INFORMATION

Freeze protection: -35°C

<b>Appearance</b>	:	Clear liquid
<b>Odour</b>	:	Characteristic
<b>Solubility</b>	:	Soluble in water

Test	Method	Unit	Min.	Max.	Typical
Freezing Point		°c		-40	
Density	ASTM D792	@ 15°c			1.069

#### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

#### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

