

## Granville FS-GX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Granville FS-GX 5W/30 is a high performance fully synthetic engine oil that provides protection against low speed pre-ignition (LSPI) issues associated with smaller capacity turbo-charged engines. FS-GX is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ILSAC: GF-5 & GF-6A

GM: Dexos™ 1 Gen 2, 4718M, 6094M & Dexos™ 1 Gen 3

API: SN-RC, SN, SN Plus, SP & SP RC

Chrysler: MS 6395

Honda: HTO-06



\* Image for illustrative purposes only.

### PRODUCT BENEFITS

- \* Helps resolve LSPI issues
- \* Fuel Efficient
- \* Fully Synthetic

### DIRECTIONS FOR USE

Use as per manufacturer's recommendations

### STORAGE INSTRUCTIONS

Store upright in a cool dry place out of the reach of children

### SHELF LIFE

5 years from date of manufacture

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Flammability</b>	: Non Flammable



SIZE	PART NO	BARCODE
1 Litre	1140	5020618011408
5 Litre	1141	5020618011415
20 Litre	1142	5020618011422
199 Litre	1145	5020618011453

# Granville FS-GX 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Percentage of Base Oil : 84.09

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.37
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.28
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			61.51
Density	ASTM D792	@ 15°C			0.852

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

