

Granville Hypafleet E9 5W/30

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hypafleet E9 5W/30 is a high performance fuel efficient heavy duty diesel engine oil that has been formulated using superior additives and quality base oils to produce a mid - low SAPS (sulphated ash, Phosphorus and Sulphur) engine oil that is suitable for use with exhaust after treatment systems including DPFs and SCR/EGR NOX reducing systems including the use of Adblue. This engine oil is suitable for mixed fleet applications including Euro IV, V and VI engine types.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: E4, E6, E7 & E9

API: CJ-4 & CK-4

MB: 228.51

Mack: EO-OPP

MAN: 3677

MTU Type 3.1

Renault Truck: RLD-3

Volvo: VDS-4

Scania: LDF-4



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6423	5020618064237
199 Litre	6425	5020618064251

PRODUCT BENEFITS

*Fully Synthetic

*Low SAPS (sulphated ash, Phosphorus and Sulphur)

* Ideal for Euro IV, V and VI engine types.

PRODUCT USAGE

For use in engines where this grade and specification oil is required.

DIRECTIONS FOR USE

Use as per the manufacturers instructions



Granville Hypafleet E9 5W/30

20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Store sealed and upright in a cool place out of the reach of children.

SHELF LIFE

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: 80.00%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	12		
Pour Point	ASTM D97	°C		-40	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

