

# Granville Hypafleet 10W

20 Litre & 199 Litre

## PRODUCT DESCRIPTION

Hypalube Hypafleet 10W is a mono grade engine oil manufactured from specially selected additive packages and solvent refined base oils that can be used in petrol and diesel applications requiring a monograde lubricant, is also suitable for use where recommended in transmission and hydraulic applications.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: CG-4 & SL  
MB: 228.1 & 229.1

## PRODUCT BENEFITS

- \*High quality base stocks
- \*Ideal for agricultural and off highway applications
- \*Suitable for use in static engines

## PRODUCT USAGE

For use where this viscosity and specifications are required

## DIRECTIONS FOR USE

Use as per the engine manufacturers recommendations

## STORAGE INSTRUCTIONS

Store sealed and upright in a cool place and out of the reach of children

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6521	5020618065210
199 Litre	6523	5020618065234



# Granville Hypafleet 10W

20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	4.1		5.63
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	8		8.97
Pour Point	ASTM D97	°C		-30	
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			32.88
Density	ASTM D792	@ 15°C			0.876

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

