

TECHNICAL DATA

Granville Hy-Vis Hydraulic 46

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hy-vis 46 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603 David Brown: S1.53.101 Denison Filterability: TP02100 DIN: 51524 Part 2 (HLP) Vickers: 1.286.S & 1.286.S3 ISO: 6734-4 HM

PRODUCT BENEFITS

*Excellent pumpability *Protects against oxidation and corrosion.

STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance

: Amber liquid



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	0724	5020618007241
199 Litre	0140	5020618001409



Revision: 1 | Date: 17/01/2023

Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com



TECHNICAL DATA

Granville Hy-Vis Hydraulic 46

20 Litre & 199 Litre

Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°c	ASTM D445	mm²/s	41.4	50.6	46.65
Viscosity, Kinematic 100°c	ASTM D445	mm²/s			6.88
Density	ASTM D792	@ 15°c	-	-	0.877

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com