

Granville Multi Hy-Vis 32

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Multi Hy-vis 32 hydraulic oil is a high viscosity index fluid formulated for use in a wide range of agricultural, commercial and industrial applications where recommended, they offers excellent pumpability and protect against oxidation and corrosion.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

DIN: 51524 Part 2 (HLP), 51524 Part 3 (HVLP) & 51524 Part 1 (HL)
ISO: 11158 (HL, HM, HV)
AFNOR: NF ISO 11158 (HL, HM, HV)
Vickers: 1.286.S
US Steel: 126 & 127



* Image for illustrative purposes only.

PRODUCT BENEFITS

- *High viscosity index
- *Excellent pumpability
- *Protect against oxidation and corrosion

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 20 Litre | 6551 | 5020618065517 |
| 199 Litre | 6553 | 5020618065531 |

STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and keep out of the reach of children

SHELF LIFE

5 years from date of manufacture

| | |
|--------------------------------|----------------------|
| Appearance | : Amber liquid |
| Odour | : Characteristic |
| Solubility | : Insoluble in water |
| Percentage of Biodiesel | : Nil |



Granville Multi Hy-Vis 32

20 Litre & 199 Litre

| Test | Method | Unit | Min. | Max. | Typical |
|---------------------------|-----------|--------------------|------|------|---------|
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | 28.8 | 35.2 | |

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

