

## Granville Hypafarm UTTO 10W/30

20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Hypafarm UTTO is Specially formulated for modern multi speed electronically actuated transmissions fitted in Agricultural and Off highway equipment. Can be used for oil immersed brakes and as a hydraulic fluid where recommended.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

Allison: C4

Case: MS1204, MS1205 & MS1210

CAT: TO-2

Ford: WSS-M2C134-A, WSS-M2C134-B, WSS-M2C134-C, WSS-M2C134-D, WSS-M2C159-A, WSS-M2C41-B, WSS-M2C48-B, WSS-M2C53-A, WSS-M2C86-A, WSS-M2C86-B & WSS-M2C86-C  
IMB6

John Deere: JDM 20A, JDM 20B, JDM 20C & JDM J27

Massey Ferguson: M1110, M1127, M1129A, M1135 & M1143

New Holland: 410-B & 420-A

Volvo: 97303 WB 101



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
20 Litre	6514	5020618065142
199 Litre	6516	5020618065166

### PRODUCT BENEFITS

\*Ideal for agricultural and off highway applications

\*Excellent heat transfer properties

### PRODUCT USAGE

For use where this type and specification of oil is required

### DIRECTIONS FOR USE

Use as per the component manufacturers recommendations



# Granville Hypafarm UTTO 10W/30

20 Litre & 199 Litre

## STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

## SHELF LIFE

5 years from date of manufacture

**Appearance** : Red Coloured liquid

**Odour** : Characteristic

**Solubility** : Insoluble in water

**Percentage of Biodiesel** : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	
Viscosity, CCS -25°C	ASTM D4684	mPa.s		7000	

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

