

# Granville

## FS-P 5W/30

1 Litre, 5 Litre & 20 Litre

### PRODUCT DESCRIPTION

Granville FS-P 5W/30 is a new generation, fully synthetic multi-grade engine oil formulated to meet the performance demands of the latest low emission engines which combine high performance, fuel efficiency and emission control. Manufactured to a low SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C2 oil. Suitable for Peugeot, Citroen, Honda & Toyota engines.

NOTE: This Oil is NOT suitable for Vehicles that require Low Speed Pre-Ignition (LSPI) capabilities. Suitable for vehicles up to 2017.



\* Image for illustrative purposes only.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C2  
PSA: B71 2290 (<2017)  
API: SN/CF

SIZE	PART NO	BARCODE
1 Litre	0481	5020618004813
5 Litre	0482	5020618004820
20 Litre	0479	5020618004790

### PRODUCT BENEFITS

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### PRODUCT USAGE

For engines where this specification lubricant is required

### DIRECTIONS FOR USE

As recommended by the engine manufacturer.



# Granville

## FS-P 5W/30

1 Litre, 5 Litre & 20 Litre

### STORAGE INSTRUCTIONS

Store upright and sealed in a cool, dry place out of the reach of children.

### SHELF LIFE

5 years from date of manufacture.

<b>Appearance</b>	: Amber liquid
<b>Odour</b>	: Characteristic
<b>Solubility</b>	: Insoluble in water
<b>Percentage of Biodiesel</b>	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	11
Viscosity, CCS -30°C	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.9
Pour Point	ASTM D97	°C		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			67
Density	ASTM D792	@ 15°C			0.85
Viscosity Index	ASTM D2270				156

### SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

